





The VISICO VT flash lights are developed under the concept of compactness, lightweight, economy without reducing power of flash light. Therefore, the units makes contributes to save space for the whole package and reduce burden during transportation. Combined Advanced performance and economy design together, the flash light gives a definite competitive edge for photographers, learners, hobbyists and amateurs. Different VT flash kits are ideal for portraits, still life, product, architectural photography and more.

All the features are built in an innovative housing, gives very cute visual effect. Scientific housing design holding inner electronic circuit boards firmly.

#### Main Features

Bowens adapter can fit various accessories Output Control range full to 1/32(6 stop points) Precision light output Flash shot times counting function Fast Recycling time and Flash Duration Overheating warning function Light weight, Compact and Easy to Operate
Clear Digital Display to show accurately the power level
CMOS Chip Technology

.vistarfoto.com 27 / 28

### studio Flash Series

Model Available : VT-100 VT-150 VT-200 VT-300 VT-400

Ø VISICo VT-200

### Flash Specifications

Dimensions (cm)	Weight	Accessories Included	Power Source	Overheating Warning	Bowens Adapter	Digital Display	Fuse	Triggering Voltage	Flash Tube	Colour Temperature	Triggering Method	Modelling Lamp Output	Flash Duration	Recycling Time to Full 110V-120V/60Hz	Recycling Time to Full 220V-240V/50Hz	Output Control Range	GN (2m, ISO 100) 1/60 Reflector SF-610	Power Output		ap
20x12x12 (without reflector)	0.75kg	Reflector, Power Cord(4m), Synch Cord(4m), Modelling Lamp, User Guide	AC 190-240V	Yes	Yes	Yes	4A	5V Low Voltage Trigger	"plug-in" Tube (user replaceable)	5600°K±200°K	Slave Sensor / Sync Cable / Test Button	75W	1/800th ~ 1/1200th	0.8~1.5s	0.3~1.2s	Full to 1/32 Stepless	30	100W	VT-100	
	0.85kg		AC 190-240V 50Hz or AC 100-130V 60Hz Automatic Voltage regulator Circuit											0.8~1.8s	0.4~1.3s		43	150W	VT-150	
	0.9kg													0.8~2.1s	0.5~1.8s		55	200W	VT-200	
	1.0kg													0.8~2.5s	0.6~2.0s		60	300W	VT-300	
	1.1kg													1.0~3.0s	0.8~2.3s		73	400W	VT-400	

- \* Test by SEKONIC L-758DR Light meter

  \* Due to our policy of constant product improvement we reserve the right to change equipment specifications without notice.





# 150 Creative kit

3x VT-150 Flash head +2 reflectors

3x LS-8005 Light stand (Air cushion)

1x UB-001 Soft umbrella 80cm

1x UB-003 Black/Silver umbrella 80cm

1x KB-F Kit bag

# 200 Creative kit

3x VT-200 Flash head +2 reflectors

3x LS-8005 Light stand (Air cushion)

1x UB-001 Soft umbrella 80cm

1x UB-003 Black/Silver umbrella 80cm

1x KB-F Kit bag

# 300 Creative kit

3x VT- 00 Flash head +2 reflectors

3x LS-8005 Light stand (Air cushion)

2x UB-001 Soft umbrella 80cm

1x UB-003 Black/Silver umbrella 80cm 1x KB-F Kit bag